

# SciCan's Autoclave Family

## STATIM 2000. The world's favorite handpiece autoclave.

6 MIN

### STATIM 2000 benefits:

- Ultra fast 6 minute unwrapped cycle
- 14 minute wrapped cycle
- Exceptional instrument turnover
- 10 minute Dri-Tec<sup>®</sup> drying Technology
- Single use water
- Aseptic transfer of instrument directly to the point-of-use
- Reduced instrument investment
- Prolongs instrument life




Recommended Essential  
STATIS<sup>™</sup> Instrument System

## STATIM 5000. All you need for the mid-sized practice.

9 MIN

### STATIM 5000 benefits:

- Ultra fast 9 minute unwrapped cycle
- 17.5 minute wrapped cycle
- Exceptional instrument turnover
- 15 minute Dri-Tec<sup>®</sup> drying Technology
- Single use water
- Aseptic transfer of instrument
- Reduced instrument investment
- Prolongs instrument life





## STATIM 7000. The chamber alternative.

12 MIN

### STATIM 7000 benefits:

- 12 minute unwrapped cycle
- 15 minute wrapped cycle
- 12 minute Dri-Tec<sup>S</sup> drying Technology
- Operates on tap water
- Sterilizes up to 10 pouched packages
- Holds two 8" x 11" instrument management cassettes
- RFID seal technology
- Easy serviceability
- Removable water reservoir



## Bravo. The ultimate Statim companion.

19 MIN

### Bravo™ benefits:

- Fast cycle times
- Fractionated vacuum system
- Intelligent closed door drying with Dri-Tec<sup>V</sup> technology
- Single use Pull'n Push water system
- Easy to use – single button operation
- Conforms to international and national standards
- Integrated printer option
- Patented door locking mechanism and steam generation system
- 17L or 21L chamber capacity
- 120V or 220V options
- 2 Year warranty



Cycle	Unwrapped	Wrapped	Rubber/Plastic	Heavy Duty Unwrapped / Air Drying
<b>STATIM 2000</b> Sterilization time Sterilization Temp Total Cycle time*	3.5 minutes 135° C 6 minutes	10 minutes 135° C 14 minutes	15 minutes 121° C 20 minutes	Air drying only Air drying only Air drying only
<b>STATIM 5000 (CANADA)</b> Sterilization time Sterilization Temp Total Cycle time*	3.5 minutes 134° C 9 minutes	6 minutes 134° C 17.5 minutes	15 minutes 121° C 24 minutes	6 minutes 134° C 12 minutes
<b>STATIM 5000 (USA)</b> Sterilization time Sterilization Temp Total Cycle time*	3.5 minutes 132° C 9 minutes	6 minutes 132° C 17.5 minutes	35 minutes 121° C 45 minutes	6 minutes 132° C 12 minutes
<b>STATIM 7000</b> Sterilization time Sterilization Temp Total Cycle time*	3.5 minutes 134° C 12 minutes	3.5 minutes 134° C 15 minutes	30 minutes 121° C 37 minutes	Air drying only Air drying only Air drying only

Total Cycle time including drying <sup>⊕</sup>	Porous/Hollow † Wrapped	Hollow † Unwrapped	Solid Wrapped	Solid Unwrapped
Bravo <sup>17</sup>	40 minutes	35 minutes	30 minutes	22 minutes
Bravo <sup>17v</sup>	35 minutes	27 minutes	24 minutes	19 minutes
Bravo <sup>17</sup>	40 minutes	32 minutes	28 minutes	23 minutes

\* Cycle time is dependent on instrument load

⊕ Cycle times represent 220V units. Cycle times for 110V units estimated up to 7 minutes longer. Sterilization temperature and hold time for stated cycles are 134°C for 4 minutes.

† Hollow instruments type "A" and "B" according to EN 13060:2004 (ie. dental handpieces, Phaco instruments, trocars, rigid scopes, etc.)

Visit [www.scican.com](http://www.scican.com) or call us toll-free for more information today.



### STATIM

#### Unit size (L x W x H):

2000: 19" x 16.25" x 6" or 48 cm x 41.5 cm x 15 cm  
 5000: 21.75" x 16.25" x 7.5" or 55.5 cm x 41.5 cm x 19 cm  
 7000: 23.8" x 22.1" x 10.7" or 60.5 cm x 56.1 cm x 27.1 cm

#### Electrical Rating:

2000: 110-120 VAC, 50/60 Hz, 15A, 1300 W  
 5000: 110-120 VAC, 50/60 Hz, 15A, 1300 W  
 7000: 208-240 VAC, 50/60 Hz, 15A, 3000W

#### Sterilization Cassette Volume / Internal Dimension (volume / L x W x H):

2000: 0.5 gal / 11" x 7" x 1.5" or 2.1 L / 28 cm x 18 cm x 3.5 cm  
 5000: 0.8 gal / 15" x 7" x 3" or 5.0 L / 38 cm x 18 cm x 7.5 cm  
 7000: 1.66 gal / 13.5" x 8.6" x 2.5" or 6.3 L / 34.3 cm x 21.9 cm x 6.4 cm

#### Weight without water:

2000: 46 lbs / 21 kg  
 5000: 72 lbs / 33 kg  
 7000: 93 lbs / 42 kg

### Bravo

#### Unit size (L x W x H):

17/17V: 22" x 19" x 16.5" or 56 cm x 48 cm x 42 cm  
 21V: 25" x 19" x 16.5" or 63.5 cm x 48 cm x 42 cm

#### Electrical Rating:

Available in 120 V, 60 Hz, 15A, 1700 W or  
 220/230V, 60 Hz, 10A, 2300 W

#### Sterilization Cassette Volume / Internal Dimension (volume / D x L):

17/17V: 4.5 gal / 10" x 13.5" or 17 L / 25.4 cm x 34.3 cm  
 21V: 5.5 gal / 10" x 17.5" or 21 L / 25.4 cm x 44.5 cm

#### Weight without water:

17: 121 lbs / 55 kg  
 17V: 128 lbs / 58 kg  
 21V: 139 lbs / 63 kg

CANADA: SciCan Ltd. 1440 Don Mills Road, Toronto, Ontario M3B 3P9 / Phone (416) 445-1600 Fax (416) 445-2727 Toll free 1-800-667-7733 [custservice.ca@scican.com](mailto:custservice.ca@scican.com)

USA: SciCan, Inc. 701 Technology Drive, Canonsburg PA, 15317 / Phone (724) 820-1600 Fax (724) 820-1479 Toll free 1-800 572-1211 [uscustmerservice@scican.com](mailto:uscustmerservice@scican.com)

STATIM, STATIM Cassette Autoclave and HYDRIM are registered trademarks of SciCan Ltd.  
 Bravo, SysTM, STATIS, Dri-Tec<sup>®</sup>, Dri-Tec<sup>®</sup>, Dri-Tec<sup>®</sup>, Dri-Tec<sup>®</sup> logos are trademarks of SciCan Ltd

